.78 .22 .10 -1.19 1.12 .13 .94 .86 59.34° .41 .13 1.19 -R.05 R.03

ISOMETRIC VIEW Expansion: .25" Standard Materials: EPDM SILICONE Optional Materials: Setup May Apply NEOPRENE NITRILE BUTYL FKM Available Corners: Face/Axial Seals 90° Molded Corners Bend Radius: Min. Dia. = 7" ID DATE

			UNLESS OTHERWISE SPECIFIED:		NAME	DATE				
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DYNAMIC RUBBER, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF			DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ± INTERPRET GEOMETRIC	DRAWN	I.Solis	10/13/2009				
				CHECKED						
				ENG APPR.				D	У Р.	
				MFG APPR.						
				Q.A.			Dyna	mic Rub	ber,	Inc.
			TOLERANCING PER:	COMMENTS:						
			MATERIAL				SIZE DWG. NO.			REV 1
	NEXT ASSY	USED ON	FINISH				A	DR112		
DYNAMIC RUBBER, INC. IS PROHIBITED.	APPLICATION		DO NOT SCALE DRAWING				SCALE: 1:2	WEIGHT:	SHEET 1 OF 1	
5	4		3			2		1		