

ISOMETRIC VIEW Expansion: .5" Standard Materials: EPDM Optional Materials: Setup May Apply SILICONE NEOPRENE NITRILE BUTYL FKM Available Corners: Face/Axial Seals Not Available - Setup May Apply

Bend Radius: Min. Dia. = 4" ID

| 5 | | 4 | | 3 | | | 2 | | | 1 | | |
|--------|---|-------------|---------|---|-----------------|-------------|------------|------|----------------------|----------|----------|--------|
| R V | PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DYNAMIC RUBBER, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITEN PREMISSION OF DYNAMIC RUBBER, INC. IS PROHIBITED. | APPLICATION | | DO NOT SCALE DRAWING | | | | SCAL | E: 1:1 | WEIGHT: | SHEET | 1 OF 1 |
| | | NEXT ASSY | USED ON | FINISH | | | | Α | DRI | 2_SEAL_C | DETAILED | |
| | | | | MATERIAL | | | | | E DWG. NO. | | | REV |
| | | | | INTERPRET GEOMETRIC TOLERANCING PER: | Q.A. COMMENT | | | | Dynamic Rubber, inc. | | | |
| | | | | DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL± ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ± | MFG APPR | | | | \sim | | | |
| | | | | | ENG APPR. | | | | 4 | | | 27 |
| | | | | | CHECKED | | | | | | | |
| | | | | | DRAWN | T. Thompson | 10/12/2009 | | | | | |
| | | | | UNLESS OTHERWISE SPECIFIED: | | NAME | DATE | | | | | |